



TECHNOPOWER

FPT 450
POWERED BY FPT
CR13TE6W



Genset Model	FPT 450
Engine Model	CR13TE6W
Alternator Model	TAL047B
Controller Model	DSE 6110 MKIII

PRIME RATINGS

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercial purchased power. There is no limitation to the annual hours of operation and this model can supply 10% Overload power for 1hour in 12 hours operation.

STANDBY RATINGS

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.

OUTPUT RATINGS		50Hz		60Hz	
		PRIME	STANDBY	PRIME	STANDBY
KVA POWER	KVA	450.0	494.0	477.0	541.0
KW POWER	KW	357.0	395.0	382.0	433.0
RATED SPEED	r.p.m	1500		1800	
VOLTAGE	V	230/400 240/415		110/220 220/380	

- Three Phase
- Diesel
- Liquid Cooled
- 90 Amps Battery Charging Alternator
- 28V Negative

ENGINE SPECIFICATIONS

Manufacturer	FPT
Model	CR13 TE6W
Engine Type	4-stroke
Cooling System	Liquid Cooled
Bore and Stroke	135 x 150 mm
Compression Ratio	16.5 : 1
Number of cylinders and arrangement	6/ Vertical in Line
Circuit Breaker Type	3Pole MCCB
Aspiration	Turbo Aftercooler air/air
Displacement	12.88 L



TECHNOPOWER FZC

Q4-94, SHARJAH AIRPORT INT'L FREEZONE (SAIF ZONE), SHARJAH, UAE.

Call: +971 6557 9794, Fax: +971 6557 9792, Email: sales@technopowergroup.com, Website: www.technopowergroup.com



TECHNOPOWER

FPT 450
POWERED BY FPT
CR13TE6W



ALTERNATOR SPECIFICATIONS

Manufacturer Leroy Somer

Model TAL047B

No of Bearings 1

Insulation Class H

Wires 6(12)

Ingress Protection Rating IP 23

AVR Model R150

Over speed (rpm) 2250

Voltage Regulation(steady state) +/- 0.8%

Waveform: NEMA = TIF < 50

Waveform: I.E.C. = THF < 2%

Winding pitch 2/3

Excitation System SHUNT

Radio Interference Supression is in line with European Standard EN61000-6

IP23 Protection


H Class Insulation

SHUNT Excitation System

WEIGHT AND DIMENSIONS



		OPEN	CLOSE
LENGTH	mm	3310	4806
WIDTH	mm	1390	1800
HEIGHT	mm	1783	2251.8
WEIGHT	kg	3072	4474



TECHNOPOWER FZC

Q4-94, SHARJAH AIRPORT INT'L FREEZONE (SAIF ZONE), SHARJAH, UAE.


Call: +971 6557 9794, Fax: +971 6557 9792, Email: sales@technopowergroup.com, Website: www.technopowergroup.com



TECHNOPOWER

FPT 450
POWERED BY FPT
CR13TE6W

Fuel Filter Type	Replaceable Element
Recommended Fuel	Class A2 Diesel
Fuel Tank Capacity	550 L



FUEL SYSTEM

		50Hz		60Hz			
EXHAUST	SILENCER TYPE	INDUSTRIAL					
	SILENCER NOISE REDUCTION LEVEL	22dB		22dB			
	MAX. ALLOWABLE BACK PRESSURE	kPa(mbar)		5(50)			
		PRIME	STANDBY	PRIME	STANDBY		
	EXHAUST GAS FLOW	kg/hr		1731	1731	2124	2124
	EXHAUST GAS TEMPERATURE	°C (°F)		471(880)	471(880)	491(916)	491(916)

EXHAUST SYSTEM



TECHNOPOWER FZC

Q4-94, SHARJAH AIRPORT INT'L FREEZONE (SAIF ZONE), SHARJAH, UAE.

Call: +971 6557 9794, Fax: +971 6557 9792, Email: sales@technopowergroup.com, Website: www.technopowergroup.com



TECHNOPOWER

FPT 450
POWERED BY FPT
CR13TE6W

A I R	AIR FILTER TYPE		Dry			
			50Hz		60Hz	
			PRIME	STANDBY	PRIME	STANDBY
	COMBUSTION AIR FLOW	m ³ /hr(kg/hr)	1443(1647)	1443(1647)	1760(2024)	1760(2024)
	MAX. COMBUSTION AIR INTAKE RESTRICTION	kPa(mbar)	2.0(20)		2.0(20)	

LUBRICATION SYSTEM

Oil Filter Type	Spin-on , Full Flow	
Total Oil Capacity	L	32.0
Oil Pan	L	28.0
Oil Type	ACEA E3/E5	

COOLING SYSTEM

		50Hz	60Hz
Water Pump Type	Centrifugal		
Cooling System Capacity	L	38.1	38.1
Radiator Fan Load	kWm	21.0	36.0
Radiator Cooling Airflow	m ³ /s	6.8	8.5
External Restriction to Cooling Airflow	Pa	196	196





TECHNOPOWER



AUTHORISED GOLD DISTRIBUTOR



DSE6110/20 MKIII

AUTO START & AUTO MAINS (UTILITY) FAILURE CONTROL MODULES



DSE6110 MKIII



DSE6120 MKIII

KEY FEATURES

- 4-line back-lit LCD text display
- Multiple display languages
- Five-key menu navigation
- LCD alarm indication
- Customisable power-up text and screen images.
- DSENet® expansion compatibility
- Data logging facility
- Internal PLC editor
- Protections disable feature
- Fully configurable via PC using USB communications
- Front panel configuration with PIN protection
- Power save mode
- 3-phase generator sensing and protection
- 3-phase mains (utility) sensing and protection (DSE6120 MKIII only)
- Automatic load transfer control (DSE6120 MKIII only)
- Generator current and power monitoring (kW, kvar, kVA, pf)
- Mains (utility) current and power monitoring (kW, kvar, kVA, pf) (DSE6120 MKIII only)
- kW overload alarm
- Over current protection
- Breaker control via fascia buttons
- Fuel and start outputs configurable when using CAN
- 6 configurable DC outputs
- 4 configurable analogue/digital inputs
- Support for 0 V to 10 V & 4 mA to 20 mA sensors
- 8 configurable digital inputs
- CAN, MPU and alternator frequency speed sensing in one variant
- Real time clock
- Manual and automatic fuel pump control
- Engine pre-heat and post-heat functions
- Engine run-time scheduler
- Engine idle control for starting & stopping
- Fuel level alarms
- 3 configurable maintenance alarms
- Compatible with a wide range of CAN engines, including Tier 4 engine support
- Uses DSE Configuration Suite PC Software for simplified configuration
- Licence-free PC software
- IP65 rating (with optional gasket) offers increased resistance to water ingress
- Configurable CAN read & transmitted information.
- 1 alternative configuration.

KEY BENEFITS

- Automatically transfers between mains (utility) and generator (DSE6120 MKIII only) for convenience.
- Hours counter provides accurate information for monitoring and maintenance periods
- User-friendly set-up and button layout for ease of use
- Multiple parameters are monitored & displayed simultaneously for full visibility
- The module can be configured to suit a wide range of applications for user flexibility
- PLC editor allows user configurable functions to meet user specific application requirements.

SPECIFICATIONS

DC SUPPLY

CONTINUOUS VOLTAGE RATING
8 V to 35 V Continuous
5 V for up to 1 minute

CRANKING DROPOUTS

Able to survive 0 V for 100 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries. LEDs and backlight will not be maintained during cranking.

MAXIMUM OPERATING CURRENT

260 mA at 12 V, 150 mA at 24 V

MAXIMUM STANDBY CURRENT

145 mA at 12 V, 85 mA at 24 V

CHARGE FAIL/EXCITATION RANGE

0 V to 35 V

GENERATOR & MAINS (UTILITY)

VOLTAGE RANGE
15 V to 415 V AC (Ph to N)
26 V to 719 V AC (Ph to Ph)

FREQUENCY RANGE

3.5 Hz to 75 Hz

MAGNETIC PICKUP

VOLTAGE RANGE
+/- 0.5 V to 70 V

FREQUENCY RANGE

10,000 Hz (max)

INPUTS

DIGITAL INPUTS A TO H
Negative switching

ANALOGUE INPUTS A & D

Configurable as:
Negative switching digital input
0 V to 10 V sensor
4 mA to 20 mA sensor
Resistive sensor

ANALOGUE INPUTS B & C

Configurable as:
Negative switching digital input
Resistive sensor

OUTPUTS

OUTPUT A & B (FUEL & START)
10 A DC at supply voltage

AUXILIARY OUTPUTS C, D, E, F, G & H

2 A DC at supply voltage

DIMENSIONS

OVERALL
216 mm x 158 mm x 43 mm
8.5" x 6.2" x 1.5"

PANEL CUT-OUT

184 mm x 137 mm
7.2" x 5.3"

MAXIMUM PANEL THICKNESS

8 mm
0.3"

STORAGE TEMPERATURE RANGE

-40°C to +85°C
-40 °F to +185 °F

OPERATING TEMPERATURE RANGE

NON-HEATED DISPLAY VARIANT
-30°C to +70°C
-22 °F to +158 °F

HEATED DISPLAY VARIANT

-40 °C to +70 °C
-40 °F to +158 °F

TECHNOPOWER FZC

Q4-94, SHARJAH INT'L AIRPORT FREEZONE (SAIF ZONE), SHARJAH, UAE.

CALL: +971 6557 9794, Fax: +971 6557 9792,

EMAIL: sales@technopowergroup.com, WEBSITE: www.technopowergroup.com



TECHNOPOWER

Silent Canopy



Fuel filling point with key lock



Document holder



Emergency stop button

Central lifting hook for easy lifting

Control Panel IP55 Control panel managed by DSE 6110 MKIII controller

Heavy duty Engines optimized for low fuel consumption

Alternator - 3phase and Single phase with AVR

Stainless Steel Lockable handles & Hinges

Sound proof galvanised canopy 65dB(A) @7m

In-built fuel tank made of Polypropylene with bounded base for 8hrs @full load

Reinforced anti-rollover forklift tunnels for safe handling



Easy maintenance easily removable side part



Fuel Inlet/Outlet



Exhaust pipes with exhaust heat wrap for high-performance and security



Galvanized metal sheet to increase strength & durability



Oil and coolant drain



Anti-vibration pads attenuate vibrations caused by the unit



Exhaust terminal pipe with tilting cap rain over